



US009411117B1

(12) **United States Patent**
Goodsell et al.

(10) **Patent No.:** **US 9,411,117 B1**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **CABLE MANAGEMENT DEVICE**

(71) Applicant: **HUBELL INCORPORATED**, Shelton,
CT (US)

(72) Inventors: **John P. Goodsell**, Stratford, CT (US);
Douglas P. O'Connor, Richmond, RI
(US)

(73) Assignee: **Hubbell Incorporated**, Shelton, CT
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/795,447**

(22) Filed: **Jul. 9, 2015**

(51) **Int. Cl.**
G02B 6/00 (2006.01)
G02B 6/44 (2006.01)
H01R 13/502 (2006.01)

(52) **U.S. Cl.**
CPC **G02B 6/4439** (2013.01); **H01R 13/502**
(2013.01)

(58) **Field of Classification Search**
CPC G02B 6/4439; H01R 13/502; H01R 13/42;
H01R 13/506; H01R 25/006
USPC 385/133, 134, 136, 137, 147; 439/529
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,216,987 B1 * 4/2001 Fukuo F16L 3/227
248/229.16
6,371,419 B1 * 4/2002 Ohnuki F16L 3/13
248/71

D468,996 S * 1/2003 Sarkinen D8/356
6,801,704 B1 10/2004 Daoud et al.
7,534,958 B2 * 5/2009 McNutt G02B 6/3897
174/101
7,607,938 B2 * 10/2009 Clark H04Q 1/136
385/135
7,734,138 B2 * 6/2010 Bloodworth G02B 6/4452
385/134
8,712,206 B2 * 4/2014 Cooke G02B 6/4452
385/134
2010/0108824 A1 5/2010 Patchett et al.
2010/0224737 A1 9/2010 LaFontaine et al.
2010/0310225 A1 * 12/2010 Anderson G02B 6/4455
385/135

* cited by examiner

Primary Examiner — Ellen Kim

(74) Attorney, Agent, or Firm — Dickinson Wright PLLC

(57) **ABSTRACT**

A cable management device and assembly includes an electrical structure having plurality of connectors for receiving connectors of a plurality of cables. A fixed support bar is spaced from and aligned with the connectors. A plurality of cable retainer members are coupled to the support bar for managing and aligning the bundle of cables coupled to the connectors. The cable retainers have a first open recess at a first end with a central axis extending in first direction, and a second open recess at a second end with a central axis extending in a second direction perpendicular to the first central axis. The first open recess mates with the support bar to slide along the length of the bar and rotate or pivot around the bar to orient the cables in a selected position and pattern. The second open recess has a dimension for coupling with the respective cable.

18 Claims, 4 Drawing Sheets

